

Name of Part	8-Foot K Style			10-Foot J Style			12-Foot H Style		
	Symbol	Price	Weight	Symbol	Price	Weight	Symbol	Price	Weight
Upper tower casting, 4-post.	K1	\$0.40	3.6	K1	\$0.40	3.6	H1	\$0.80	6
Upper tower casting, 3-post.	3J1	1.00	9	3J1	1.00	9			
Lower tower casting, 4-post.	K2	.40	3.3	J2	.60	4	H2	1.40	12
Lower tower casting, 3-post.	3K2	.40	2.4	3J2	.40	3.2			
Main casting with bushings.	K3	9.00	47	J3	12.00	63	H3	24.00	113
Sheave shield	K4	.60	4	J4	1.00	5	H4	1.80	10
Sheave shield with sheaves.		1.00	5.4		1.50	6.8		2.70	15
Bushing for crank gear	K5	.40	.2	X5	.80	.4	H5	1.20	.5
Bushing for main casting	K6	.50	.3	J6	.80	.5	H6	1.30	.5
Pitman guide	E7	.50	2.6	X7	.70	5	H7	1.40	8
Crank gear with shaft & bush.	K8	3.00	15	X8	4.50	25	H8	7.50	41
Pinion	E9	.70	3.3	X9	1.00	6	H9	1.80	10
Wheel hub with shaft	K10	3.00	18	J10	6.00	35	H10	11.00	59
Vane hinge, upper	E11	.20	.8	X11	.20	1.3	H11	.40	2.5
Vane hinge, lower	K12	.70	5.1	J12	1.20	8	H12	1.70	11
Latch	K13	.20	.6	J13	.30	1.1	H13	.40	1.5
Sheave	E14	.20	.6	J14	.20	.8	H14	.40	1.2
Brake	K15	.50	3.2	J15	.90	7	H15	1.30	10
Brake with rod and spring		.90	4.1		1.50	8		2.30	12
Piston eye	K16	.50	1.4	J16	.60	2	H16	.80	2.5
Pump pole socket	K17	.20	1.1	J17	.30	1.5	H17	.60	3.2
Swivel slide	K18	.30	2	J18	.40	2.5	H18a	.70	3.5
Guide for swivel slide, 4-post	K19	.30	2	J19	.40	3	H19a	.60	4
Guide for swivel slide, 3-post	3K19	.20	1.1	3J19	.20	1.3			
Pump attachment	K20	.60	2.3	K20	.60	2.3	H20	.80	3.7
Grease plunger	E21	.10	.2	E21	.10	.2	E21	.10	
Grease cup, plain	K22	.20	.3	J22	.20	.3	H22	.20	.3
Grease cup, ratchet	K23	.30	.4	J23	.30	.4	H23	.30	.4
Pitman guide pin	E52	.10	.3	X52	.20	.4	H52	.30	.7
Pitman	E53	.80	3.8	X53	1.20	6	H53	3.60	11
Piston rod with nut only	K54	.60	4.7	J54	1.00	7	H54	1.80	12
Piston with pump pole socket	E55	.80	5.8		1.30	9		2.40	15
Vane pin	E56	.20	.9	X55	.30	1.8	H55	.50	3
Brake rod	E56	.20	.6	J56	.30	1	H56	.60	1.5
Sheave pin	E59	.10	.1	J48	.10	.2	H87	.10	.3
Latch pitman	K60	.20	.3	J60	.30	.5	H60	.40	1
Vane stem	E63	2.00	10.5	X63	4.00	19	H63	8.00	37
Vane truss	E64	1.00	5	X64	1.60	8	H64	2.50	12
Vane rib, short	E65	.20	.8	X65	.40	1.5	H65	.40	1.5
Vane rib, medium short							H65 1/2	.50	2.1
Vane rib, medium	E66	.30	1.1	X66	.50	2.1	H66	.60	2.6
Vane rib, long	E67	.40	1.4	X67	.60	2.6	H67	1.00	4.3
Arm, each	E68	.80	3.8	J68	1.40	5	H68	2.50	10
Outer rim	E69	.50	2.3	X69	1.00	5	H69	1.50	7
Inner rim	E70	.20	.8	X70	.40	1.7	H70	.50	2.2
Sail clip, large	E74	.10	.2	X74	.20	.4	H74	.30	.5
Sail clip, small	E75	.10	.1	X75	.10	.2	H75	.10	.2
Swivel, complete with chain	K79	1.30	3	J79	1.80	4	H79	3.00	7
Chain end	K80	.10	.2	J80	.20	.2	H80	.30	.3
Governor spring	E82	1.00	5	X82	1.50	7	H82	3.50	16
Brake spring	E83	.10	.2	X83	.20	.2	H83	.30	.5
COMPLETED PARTS									
Wheel section, complete		3.50	13		6.00	23		8.50	35
Pull-in lever, complete		.80	1.5		1.00	1.5			

REPAIR LIST FOR MONITOR STEEL MILLS

Name of Part	8-Foot K Style			10-Foot J Style			12-Foot H Style		
	Symbol	Price	Weight	Symbol	Price	Weight	Symbol	Price	Weight
<div style="display: flex; justify-content: space-between;"> Windmill-Parts.com 940 597-7735 </div>									
Upper tower casting, 4-post.	K1	\$0.40	3.6	K1	\$0.40	3.6	H1	\$0.80	6
Upper tower casting, 3-post.	3J1	1.00	9	3J1	1.00	9			
Lower tower casting, 4-post.	K2	.40	3.3	J2	.60	4	H2	1.40	12
Lower tower casting, 3-post.	3K2	.40	2.4	3J2	.40	3.2			
Main casting with bushings	K3	9.00	47	J3	12.00	63	H3	24.00	113
Sheave shield	K4	.60	4	J4	1.00	5	H4	1.80	10
Sheave shield with sheaves		1.00	5.4		1.50	6.8		2.70	15
Bushing for crank gear	K5	.40	.2	X5	.80	.4	H5	1.20	.5
Bushing for main casting	K6	.50	.3	J6	.80	.5	H6	1.30	.5
Pitman guide	E7	.50	2.6	X7	.70	5	H7	1.40	8
Crank gear with shaft & bush.	K8	3.00	15	X8	4.50	25	H8	7.50	41
Pinion	E9	.70	3.3	X9	1.00	6	H9	1.80	10
Wheel hub with shaft	K10	3.00	18	J10	6.00	35	H10	11.00	59
Vane hinge, upper	E11	.20	.8	X11	.20	1.3	H11	.40	2.5
Vane hinge, lower	K12	.70	5.1	J12	1.20	8	H12	1.70	11
Latch	K13	.20	.6	J13	.30	1.1	H13	.40	1.5
Sheave	E14	.20	.6	J14	.20	.8	H14	.40	1.2
Brake	K15	.50	3.2	J15	.90	7	H15	1.30	10
Brake with rod and spring		.90	4.1		1.50	8		2.30	12
Piston eye	K16	.50	1.4	J16	.60	2	H16	.80	2.5
Pump pole socket	K17	.20	1.1	J17	.30	1.5	H17	.60	3.0
Swivel slide	K18	.30	2	J18	.40	2.5	H18a	.70	3.5
Guide for swivel slide, 4-post	K19	.30	2	J19	.40	3	H19a	.60	4
Guide for swivel slide, 3-post	3K19	.20	1.1	3J19	.20	1.3			
Pump attachment	K20	.60	2.3	K20	.60	2.3	H20	.80	3.7
Grease plunger	E21	.10	.2	E21	.10	.2	E21	.10	
Grease cup, plain	K22	.20	.3	J22	.20	.3	H22	.20	.8
Grease cup, ratchet	K23	.30	.4	J23	.30	.4	H23	.30	.4
Pitman guide pin	E52	.10	.3	X52	.20	.4	H52	.30	.7
Pitman	E53	.80	3.8	X53	1.20	6	H53	3.60	11
Piston rod with nut only	K54	.60	4.7	J54	1.00	7	H54	1.80	12
Piston with pump pole socket		.80	5.8		1.30	9		2.40	15
Vane pin	E55	.20	.9	X55	.30	1.8	H55	.50	3
Brake rod	E56	.20	.6	J56	.30	1	H56	.60	1.5
Sheave pin	E59	.10	.1	J48	.10	.2	H87	.10	.3
Latch pitman	K60	.20	.3	J60	.30	.5	H60	.40	1
Vane stem	E63	2.00	10.5	X63	4.00	19	H63	8.00	37
Vane truss	E64	1.00	5	X64	1.60	8	H64	2.50	12
Vane rib, short	E65	.20	.8	X65	.40	1.5	H65	.40	1.5
Vane rib, medium short							H65 1/2	.50	2.1
Vane rib, medium	E66	.30	1.1	X66	.50	2.1	H66	.60	2.6
Vane rib, long	E67	.40	1.4	X67	.60	2.6	H67	1.00	4.3
Arm, each	E68	.80	3.8	J68	1.40	5	H68	2.50	10
Outer rim	E69	.50	2.3	X69	1.00	5	H69	1.50	7
Inner rim	E70	.20	.8	X70	.40	1.7	H70	.50	2.2
Sail clip, large	E74	.10	.2	X74	.20	.4	H74	.30	.5
Sail clip, small	E75	.10	.1	X75	.10	.2	H75	.10	.2
Swivel, complete with chain	K79	1.30	3	J79	1.80	4	H79	3.00	7
Chain end	K80	.10	.2	J80	.20	.2	H80	.30	.3
Governor spring	E82	1.00	5	X82	1.50	7	H82	3.50	16
Brake spring	E83	.10	.2	X83	.20	.2	H83	.30	.5
COMPLETED PARTS									
Wheel section, complete		3.50	13		6.00	23		8.50	35
Pull-in lever, complete		.80	1.5		1.00	1.5			